



NATURAL VENEER

PRODUCT SPECIFICATION

Natural veneer, also called sliced hardwood, standard veneer, is a thin sheet of hardwood, usually thinner than 3 mm. It may be sliced horizontally or peeled into sheets.

Natural veneer is used for as decorative wood covers in decorative interior design, furniture constructions, doors, window frames, wall and ceiling panels, automotive interiors and in decorative object constructions.



STANDARD DIMENSIONS (CUSTOM DIMENSIONS BY REQUEST)

LENGTH	Varies from log to log, more information on request
WIDTH	100 mm & wider
THICKNESS	Depending on the species: ~0.5 mm. Other thicknesses such as 0.9 mm, 1.5 mm or 2,5 mm are also on stock. We slice different thicknesses precisely by order (thinner or thicker than standard). We also have an extensive range of sliced wood in 3.0 mm and even 4.0 mm (see flooring lamellas)
WOOD MOISTURE	~10-14 %

SPECIES ON STOCK (OTHERS BY REQUEST)

NORTH AMERICA



American Walnut

American White Oak

Hard Maple

Red Oak

Black Cherry

White Ash



Poplar (Tulipwood)

Carolina Pine

Hickory

Red Gum

EUROPE



European Ash White

European Oak

European Oak Knotty

European Beech

European Birch

Sycamore




European Larch

European Alder



SPECIES ON STOCK (OTHERS BY REQUEST)


AFRICA



Sapelli



Anigré



Etimoé



Khaya



Makoré

PROCESSING INFORMATION

Veneer can be processed with standard machines. Dust is generated mostly in large particle sizes but can accumulate in the wood fuel collection system and in the sawmill. Regular cleaning is important to reduce electrical hazards. When working with the products, the usual protective measures must be taken: hearing protection, gloves, dust mask (when cleaning) and safety glasses.



The mark of
responsible forestry

