



SLICED HARDWOOD

PRODUCT SPECIFICATION

Sliced Hardwood, also called veneer, is a thin sheet of hardwood, usually thinner than 3 mm. It may be sliced horizontally or peeled into sheets.

Sliced Hardwood is used for as decorative wood covers in decorative interior design, furniture constructions, doors, window frames, wall and ceiling panels, automotive interiors and in decorative object constructions.

STANDARD DIMENSIONS (CUSTOM DIMENSIONS BY REQUEST)

LENGTH	Varies from log to log, more information on request
WIDTH	100 mm & wider
THICKNESS	Depending on the species: ~0.5 mm. Other thicknesses such as 0.9 mm, 1.5 mm or 2,5 mm are also on stock. We slice different thicknesses precisely by order (thinner or thicker than standard). We also have an extensive range of sliced wood in 3.0 mm and even 4.0 mm (see flooring lamellas)
WOOD MOISTURE	~10-14 %

SPECIES ON STOCK (OTHERS BY REQUEST)

NORTH AMERICA



American Walnut



American White Oak



Hard Maple



Red Oak



Black Cherry



White Ash



Poplar
(Tulipwood)



Carolina Pine



Hickory



Red Gum

EUROPE



European Ash
White



European Oak



European Oak
Knotty



European Beech



European Birch



Sycamore



European Larch



European Alder

SPECIES ON STOCK (OTHERS BY REQUEST)

AFRICA



Sapelli



Anigré



Etimoé



Khaya



Makoré

PROCESSING INFORMATION

Veneer can be processed with standard machines. Dust is generated mostly in large particle sizes but can accumulate in the wood fuel collection system and in the sawmill. Regular cleaning is important to reduce electrical hazards. When working with the products, the usual protective measures must be taken: hearing protection, gloves, dust mask (when cleaning) and safety glasses.



The mark of
responsible forestry

